

accu-jet[®] S Pipette Controller



The NEW accu-jet S pipette controller stands alone as a versatile and well-balanced addition to your lab.

It makes lab work simple, easy and efficient, whether you use it for cell culture work, reagent preparation, or general pipetting. Adjust power and precision on the fly, with pressure sensitive buttons that smoothly control pipetting speed, and achieve precise meniscus control when used with pipettes as small as

0.1 mL. The new well-balanced design features an ergonomic

grip for comfortable uninterrupted use, and the integrated rest position lets you put it down without sacrificing the cleanliness or sterility of your serological pipette.

A wall mount also provides additional storage, freeing up space on your work area for disinfection or decontamination tasks. It's quick and convenient, and ready when you are.

accu-jet S

Color	Cat. No.		
anthracite	26350		
berry	26351		
petrol	26352		
amethyst	26353		
(100-240 V/50-60 Hz) Universal AC adapter included.			

Efficient single-handed operation

Wall mount for space-saving storage

Replacement parts for the accu-jet S pipette controller

Description	Cat. No.
Universal AC adapter	26606
Snap tape	26547
Wall support	26539
NiMH battery	26630
Silicone adapter with non-return valve	26508



	Membrane filters for accu-jet S pi	ipette controller
Description Pack of	Description	Pack of

Description Pa	ack of (Cat. No.
0.2 µm, sterile	1	26530
0.2 µm	10	26535
3 µm	1	26052
3 µm	10	26056

BRANDTECH.

accu-jet[®] S Pipette Controller

accu-jet S Highlights

- For glass and plastic pipettes from 0.1 to 200 mL
- Four attractive colors
- Two color charge indicator LED/light •
- NiMH battery with intelligent charging technology lasts up to 8 hours.
- Ergonomic handgrip with a lightweight, well-balanced design
- Quick: Fills a 25 mL pipette at maximum • motor speed in only 3 seconds
- Adapter, adapter housing and filter are autoclavable





Rest position with inserted pipette

the new accu-jet S





Gravity delivery or blow-out with motor power



Direct outlet of sample vapors



Membrane filter and check valve prevent liquid penetration and over-aspirating liquid



Smart charging technology prevents lazy battery effect



Charging indicator

possible with the charging cable connected.